



ANTI-MOISSISSURES

GRÂCE À SA FORMULE DE MOUSSE ACTIVE, ANTI-MOISSISSURES DÉTRUIT IMMÉDIATEMENT LES MOISSISSURES ET LES ALGUES. RÉSULTAT EN 10



DESCRIPTION DU PRODUIT

Anti-moisissures détruit immédiatement les moisissures et les algues sur les murs, les sols et les joints tant à l'intérieur qu'à l'extérieur. Anti-moisissures convient également pour traiter tant les grandes superficies que les taches tenaces et les endroits difficiles d'accès grâce à la combinaison unique d'un spray et de mousse. Résultat en 10 minutes.

DOMAINE D'APPLICATION

Murs, sols et joints dans les espaces sanitaires, les cuisines, les caves et les garages, entre autres. Convient également pour des applications à l'extérieur, comme pour les façades, les balcons et les jardinières.

PROPRIÉTÉS

Détruit immédiatement les moisissures, les algues et la mousse
Formule de mousse active Combinaison unique d'un spray (grande superficie) et de mousse (taches tenaces) Résultat en 10 minutes Pour une utilisation à l'intérieur et à l'extérieur

PRÉPARATION

Conditions de mise en œuvre: Ne pas utiliser à des températures $\leq +5$ °C.

Exigences des surfaces: Do not use on acid-sensitive materials, such as marble and stone.

Pré-traitement des surfaces: Ne pas éliminer les moisissures et les algues au préalable.

MISE EN OEUVRE

Garantie: For 4-6 m² of walls or 12-16 m of joints.

Mode d'emploi:

Prepare the spray cap by pulling the trigger to unlock the child safe trigger and rotate the nozzle a quarter turn. Prevent spattering: always prepare first and only then spray.

Prepare the spray cap by pulling the trigger to unlock the child safe trigger and rotate the nozzle a quarter turn. Prevent spattering: always prepare first and only then spray.

Do not remove mould and algae prior to treatment. Scrape off moss layers. Pull trigger to unlock the child safety and rotate the nozzle a quarter turn. Avoid splashes: first prepare nozzle for use and only then spray. Spray the surface from 3-5 cm and leave for 10 minutes. In bad cases repeat treatment after 10 minutes. Clean the treated surface thoroughly with sponge and water. In case of elastic joints (e.g. silicone sealants) repeat the entire treatment (spraying and cleaning). After use close trigger by rotating nozzle downwards into the child safe position.

Taches/résidus: Stains are not removable.

Points d'attention: Cover plants and metal. Avoid splashes on clothing (bleach stains), on gloss paint (matting) and blinds (discoloration). Rinse immediately with water in case of contact. Ventilate well during use. Can cause a brown discoloration on light-colored elastic joints and on delicate tiles. Use on (spack) sprayed ceilings and walls is not advisable. Can loosen loose coatings. It is always advisable to do a test in an inconspicuous place before use. Do not reuse bottle. Do not use in combination with other products, it could release dangerous gases (chlorine). In case of contact with the skin, rinse immediately with water.

SPÉCIFICATIONS TECHNIQUES

Matière première de base:	Hypochlorite de sodium 50 g/l, pourcentage de chlore actif environ 5 %
Couleur:	Jaune clair
Densité env.:	1.09 g/cm ³
Valeur du pH env.:	13
Viscosité:	Liquide

CONDITIONS DE STOCKAGE

Conserver le flacon fermé correctement et en position verticale dans un endroit stable, sec, frais et à l'abri du gel.

Nos conseils sont basés sur des recherches étendues et des expériences pratiques. En raison de la grande diversité de matériaux et/ou de conditions d'utilisation de nos produits, nous ne pouvons accepter aucune responsabilité pour les résultats obtenus et/ou pour des dommages éventuels qui résulteraient de l'usage du produit. Nous sommes cependant à votre entière disposition pour vous offrir des conseils.