



GRIZZLY MONTAGE POWER

SUPER STRONG ADHESIVE WITH HIGH FINAL STRENGTH FOR INTERIOR USE



PRODUCT DESCRIPTION

An universal and super strong construction adhesive for interior use, with permanent elasticity and high final strength. For bonding all kinds of objects onto porous surfaces.

FIELD OF APPLICATION

Suitable for all kinds of materials: e.g. Wood, metals, stone, plastics (test in advance), ceramic, glass, cork, polystyrene foam and many more onto porous surfaces (e.g. wood, stone, concrete, plaster, chipboard). To all kinds of objects: e.g. skirting boards, laths, window sills, tear plates, thresholds, fascia boards, plate material, insulation material, stair steps, ceramic tiles, polystyrene ornaments and borders.

Not suitable for PE, PP, PTFE, bitumen, mirrors, natural stone, permanently moist places and for attaching a non-porous material on a non-porous substrate. When gluing plastics always perform an adhesion test first. Adhesion to plastics can vary depending on the type of synthetic and the quality of the plastic.

PROPERTIES

- Very high final bond strength
- For all materials
- Suitable for porous and uneven surfaces
- Flexible
- For interior use
- Easy to apply
- Filling
- Solvent & acid free
- Correctable
- Moisture resistant
- Temperature resistant

PREPARATION

Working Conditions: Only apply at temperatures between +5 °C and +40 °C.

Surface Requirements: Both parts must be dry, clean and free of dust and grease. One of the two parts must be porous (absorbent).

Tools: Use Bison Power Pistol to apply adhesive. Knife or Bison Multi Tool to open the cartridge. If necessary, use a rubber mallet to tap surface lightly. For surface bonding use a glue spreader (2 mm).

APPLICATION

Coverage: Wall covering sheets and panels: about 5-8 m²/kg depending on the weight of the material. Lathing, skirting boards and timber framework: about 4-6 m²/kg glued surface.

Directions for use:

Before using open cartridge at the top by cutting off the plastic nipple above the thread with a multitool. Fix the nozzle onto the cartridge and cut at an angle to the desired diameter.

Cut off screw thread, assemble nozzle and cut to a diameter of at least 0.5 cm.

Depending on the weight of the material, apply the adhesive evenly in strips or dots at intervals of between 20 and 30 cm.

Always apply adhesive to the corners and along the edges.

For surface bonding apply adhesive thinly and evenly on one side using a glue spreader. Assemble materials with a pushing movement and press or knock firmly together. Correction is still possible. For heavy materials fasten or support where necessary.

Stains/residue: Use water for cleaning tools and removing wet adhesive residue. Dry adhesive residue can only be removed mechanically.

TECHNICAL SPECIFICATIONS

Chemical base:	Acrylic dispersion
Chemicals resistance:	Good
Colour:	Cream
Density approx.:	1.50 g/cm ³
Filling capacity:	Good
Final bond strength after:	24 hours
Minimum temperature resistance:	-20 °C
Maximum temperature resistance:	80 °C
Paintability:	Very good
Solid matter approx.:	75 %
UV resistance:	Very good
Viscosity:	Pasty
Water resistance:	Limited

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.



GRIZZLY MONTAGE POWER

SUPER STRONG ADHESIVE WITH HIGH FINAL STRENGTH FOR INTERIOR USE

STORAGE CONDITIONS

Close container properly and store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.